

INOX | Blast Chillers

Blast chillers

RF 50A



The items can be supplied either with adjustable feet or lockable castor

Inner fan cover

GAS
R290

60 mm

5
CLIMATIC CLASS
40°C

Needle probe

Anti-condensation "thermal-braker" on door frame

DETAILS



The items can be supplied either with adjustable feet or lockable castor



Inner fan cover



Needle probe



Digital control



Suitable for tray
EURONORM
600x400mm or
GASTRONORM
GN1/1



Anti-condensation
"thermal-braker" on
door frame



Evaporator with
anti-corrosion
treatment

GENERAL FEATURES

- GNI/1 and EURONORM 600x400mm Upright Blast chiller
- Stainless Steel exterior and interior
- Ventilated Cooling with Manual defrost
- Plastic thermal-braker as chamber body frame (Hot pipe system)
- Evaporator with anti-corrosion treatment
- Foaming Agent Cyclopentane (60mm per side - CFC Free)
- Digital Thermostat with Buzzer alarm
- Error message directly in the display
- Chilling chamber in stainless steel
- Door microswitch for stop inner fan with open door
- Prepared for condensation water tray (Not included)
- Reversible door / Needle probe fitted as standard
- Tray configuration: 65mm distance between trays
- N.4 S/S Adjustable feet - (Lockable castor as Optional)
- Temperature controlled or temporized blast cycles (Soft/Hard)
- Automatic storage mode at the end of blast chilling cycle
- ECM Fan (For Low energy consumption/Low noise level)
- Separate button for "ICE CREAM" Cycle
- Separate button for "-40°C" Cycle
- ICE CREAM kit (PANS not included) optional

TECHNICAL SPECIFICATIONS

Capacity	Ch.15Kg/Fr.10Kg
Temperature	+10°C ~ -40°C
Consumption	N/A kWh/24h
Rated Power	749 W
Noise level	60 dB(A)
Net Weight	76 Kg
Gross Weight	86 Kg
External Dimensions (WxDxH mm)	760x725x850
Internal Dimensions (WxDxH mm)	640x405x360
Packaging dimensions (WxDxH mm)	800x760x900
Loading quantities 20'/40'/40'HQ	42/86/126

CERTIFICATION

CE RoHS

PRODUCT DIMENSIONS

